

175W Solar Module High Efficiency Back-Contact

- Sunny Apex's HOP series solar modules ranged from 35Watt to 175Watt
- Aesthetically using clear surface back-contact cells
- Cells with High conversion efficiency above 24%
- Anodized aluminum improving corrosion resistance
- Excellent performance under low light conditions



O Your best choice for off-grid solar application ! *O*

Electrical Specifications


Model Type	SA-H175	SA-H175
Peak Power (Pmax)	175W	175W
Module Efficiency	20.30%	20.30%
Maximum Power Voltage (Vmp)	22.1V	44.1V
Maximum Power Current (Imp)	7.93A	3.97A
Open Circuit Voltage (Voc)	25.9V	51.9V
Short Circuit Current (Isc)	8.37A	4.19A
Power Tolerance	olerance -5% / + 10%	
Maximum System Voltage	70V	
Norminal Operating Cell Temp. 46 °C (+/- 2		(+/- 2)

Mechanical Specifications

Cell type	Back contact high eff. Mono
Number of cells	Total 144 cells, 36 cells in series
Weight	10.77kg [23.74lbs]
Dimensions	1082 x 796 x 35mm
	[42.55 x 31.36 x 1.38in]
Frame	$> 15 \mu m$ clear anodized aluminum
Junction Box	IP 65 waterproof
Cables	4.00mm ² , 900mm
Connectors	MC4 compatible


Temperature Coefficients

Power	-0.27%/°C
Voltage	-0.236%/°C
Current	0.058%/°C



Warranties & Certifiations

Warranties	2 years product warranty, 20 years limited power	
	warranty of 80% of the mnimum specificed power rating	
Certificates	CE	



Unit: mm [inch]

Note: All electrical parameters are rated at standard test conditions (irradiance of 1000W/m2. AM 1.5G, cell temperature 77°F/25°C)

Caution: Read Safety and Installation Instruction before using this product.

2021 Sunny Apex Development Ltd. All right reserved. Specifications included in this datasheet are subject to change without notice.

Sunny Apex Development Limited

www.sunnyapex.com